

CARACTERÍSTICAS TÉCNICAS CALDERAS SY-GB-HS

	PRODUCCIÓN DE VAPOR	POTENCIA	SUPERFICIE DE CALEFACCIÓN	VOLÚMEN TOTAL	PRESIONES DE DISEÑO
	KG/H	KW	M2	LITRO	bar
HS 400	700	540	12,94	920	9, 11, 13 y 15
HS 500	900	670	15,65	1111	9, 11, 13 y 15
HS 600	1100	785	15,94	1038	9, 11, 13 y 15
HS 800	1200	1050	17,03	1164	9, 11, 13 y 15
HS 1000	1700	1275	23,84	991	9, 11, 13 y 15
HS 1200	2000	1400	35,14	1243	9, 11, 13 y 15
HS 1500	2600	1960	44,5	2490	6.5, 9, 11, 13 y 15

DIMENSIONES GENERALES CALDERAS SY-GB-HS

	ALTURA	DIÁMETRO	ANCHO	LARGO	BANCADA
	(SIN ACCESORIOS)	(SIN ACCESORIOS)	(CON ACCESORIOS)	(SIN QUEMADOR)	
HS 400	1730 mm	1360 mm	2060 mm	2450 mm	1750x800
HS 500	1795 mm	1410 mm	2110 mm	2470 mm	2000x840
HS 600	1795 mm	1410 mm	2110 mm	2470 mm	2000x840
HS 800	1840 mm	1520 mm	2130 mm	2690 mm	2000x860
HS 1000	1940 mm	1620 mm	2225 mm	2690 mm	2000x900
HS 1200	2160 mm	1780 mm	2450 mm	2900 mm	2000x1040
HS 1500	2350 mm	1970 mm	2600 mm	2880 mm	2000x1190